acc. to 29 CFR 1910.1200 App D

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

CERAKUTE

SECTION 1: Identification

INNOVATIONS OF NIC INDUSTRIES

1.1 Product identifier

Trade name

AHW-104 Rapid Ceramic Paint Sealant

Revision: 07/23/2024

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Consumer use (private households) Automotive Restoration

1-800-633-8253 (USA & Canada)

1.3 Details of the supplier of the safety data sheet

PRISMATIC POWDERS

NIC Industries, Inc 7050 6th St. White City Oregon 97503 United States

Telephone: 866-774-7628 e-mail: sds@nicindustries.com Website: www.nicindustries.com

1.4 Emergency telephone number

Emergency information service

The information contained in this Safety Data Sheet (SDS) is, to the best of our knowledge, true and accurate and presented in good faith. NIC Industries, Inc. makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. Because many factors may affect processing or application/use of this product, this data is offered solely for the user's consideration, investigation and verification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or process. Regulatory requirements are subject to change and may differ from one location to another. It is the responsibility of the buyer/user to ensure its activities comply with all local, state and federal regulations.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200) This mixture does not meet the criteria for classification.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200) Not required.

- Hazardous ingredients for labelling

Refractory Resin, Curing Agent

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of \geq 0.1%.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

3.2 Mixtures

Description of the mixture

Name of substance	ldentifier	Wt%
DI Water	CAS No 7732-18-5	≥ 90
Flow Agent	CAS No Trade Secret	1 - < 5
70% Isopropanol	CAS No 67-63-0	0.1 - < 1
Acetic Acid 99%	CAS No 64-19-7	0.1 - < 1
Refractory Resin	CAS No Trade Secret	0.1 - < 1
Ambient Curable Refractory Resin	CAS No Trade Secret	0.1 - < 1
Curing Agent	CAS No Trade Secret	0.1 - < 1
Capping Agent	CAS No Trade Secret	0 - < 0.1
Coupling Agent	CAS No Trade Secret	0 - < 0.1
Catalyst	CAS No Trade Secret	0 - < 0.1
Silicon Based Carrier Solvent	CAS No Trade Secret	0 - < 0.1

Remarks

** Trade Secret: In accordance with OSHA Hazard Communication Standard 29 CFR 1910.1200(i) and in accordance with the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS), the specific identity and/or exact percentage (concentration) of the composition has been withheld as a "Trade Secret"

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

Revision: 07/23/2024



acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

Revision: 07/23/2024

- **4.2 Most important symptoms and effects, both acute and delayed** Symptoms and effects are not known to date.
- **4.3** Indication of any immediate medical attention and special treatment needed None.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Water spray, Dry extinguishing powder, BC-powder, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder.

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

Revision: 07/23/2024

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupa	Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of substance	ldentifi- er	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Nota- tion	Source
US	Acetic Acid 99%	PEL (CA)	10	25	15	37	40			Cal/OSHA PEL
US	Acetic Acid 99%	REL	10 (10 h)	25 (10 h)	15	37				NIOSH REL
US	Acetic Acid 99%	TLV®	10		15					ACGIH® 2023
US	Acetic Acid 99%	PEL	10	25						29 CFR 1910.100 0
US	70% Isopropanol	TLV®	200		400					ACGIH® 2023
US	70% Isopropanol	PEL (CA)	400	980	500	1,225				Cal/OSHA PEL
US	70% Isopropanol	REL	400 (10 h)	980 (10 h)	500	1,225				NIOSH REL
US	70% Isopropanol	PEL	400	980						29 CFR 1910.100 0

<u>Notation</u>

Ceiling-C

ceiling value is a limit value above which exposure should not occur

STEL

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

INNOVATIONS OF NIC INDUSTRIES

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

Revision: 07/23/2024

<u>Notation</u>

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours timeweighted average (unless otherwise specified

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection Wear protective gloves.
- Other protection measures

Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid
Color	White
Particle	Not relevant (liquid)
Particle size	Not available
Odor	Characteristic

Other safety parameters

pH (value)	Not determined
Melting point/freezing point	Not determined
Initial boiling point and boiling range	100 °C
Flash point	>90 °C
Evaporation rate	Not determined
Flammability (solid, gas)	Not relevant (fluid)

CERAKOTE PRISMATIC POWDERS

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

Revision: 07/23/2024

Explosive limits	Not determined
Vapor pressure	33.2 Pa at 25 °C
Density	0.99 ^g / _{cm³}
Vapor density	Not available
Relative density	Not available
Solubility(ies)	Not determined
Partition coefficient	
- n-octanol/water (log KOW)	Not available
Auto-ignition temperature	368 °C
Decomposition temperature	Not relevant
Viscosity	Not determined
- Kinematic viscosity	Not determined
Explosive properties	None
Oxidizing properties	None
	Hazard classes acc. to GHS (Physical hazards): Not relevant
Flammable liquids	
- Sustained combustibility	No
Other information	
Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment: 300°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

9.2

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Reacts with water.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Moisture.

10.5 Incompatible materials

Oxidizers, Alcohols. Amines. Water.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

Revision: 07/23/2024

10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, and silicon oxides may be produced from all coating formulations. Chlorine-containing gases, fluorine-containing gases may be produced in products containing p-chlorobenzotrifluoride. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

This mixture does not meet the criteria for classification.

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ΑΤΕ
Ambient Curable Refractory Resin	Trade Secret	Oral	2,000 ^{mg} / _{kg}
Refractory Resin	Trade Secret	Oral	>300 ^{mg} / _{kg}
Curing Agent	Trade Secret	Oral	500 ^{mg} / _{kg}
Capping Agent	Trade Secret	Oral	851 ^{mg} / _{kg}
Capping Agent	Trade Secret	Dermal	547 ^{mg} / _{kg}

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance Classification Number			
70% Isopropanol	3		

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

Revision: 07/23/2024

Specific target organ toxicity - single exposure Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability Data are not available.

12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

12.4 Mobility in soil Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of \ge 0.1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \ge 0.1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/packaging disposal

Do not empty into drains. Avoid release to the environment. Contact a licensed professional waste disposal service to dispose of this material and its packaging.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Hazardous waste code(s)

The waste code(s) should be assigned in discussion between the user and the waste disposal company.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- 14.1 UN number
- 14.2 UN proper shipping name
- 14.3 Transport hazard class(es)
- 14.4 Packing group

not subject to transport regulations not relevant

none

not assigned

CERAKOTE PRISMATIC

INNOVATIONS OF NIC INDUSTRIES

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

Revision: 07/23/2024

14.6 Remarks

14.7 Transport in bulk according to IMO instruments The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

None of the ingredients are listed.

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	Effective date
70% Isopropanol	12/31/1986

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	Statutory code	Final RQ pounds (Kg)
Acetic Acid 99%	1	5000 (2270)

Legend

"1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

Clean Air Act

None of the ingredients are listed.



acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

Revision: 07/23/2024

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Acetic Acid 99%			1.0 %
70% Isopropanol			1.0 %

- Hazardous Substance List (NJ-RTK)

Name of substance	Classifications
Capping Agent	CO F3 R1
Acetic Acid 99%	CO F2
70% Isopropanol	F3

Legend

- CO Corrosive
- F2 Flammable Second Degree
- F3 Flammable Third Degree
- R1 Reactive First Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Classification
Acetic Acid 99%	E
70% Isopropanol	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	References
Acetic Acid 99%	T, F
70% Isopropanol	T, F
Catalyst	Т

<u>Legend</u>

F Flammability (NFPA®)

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

None of the ingredients are listed.

VOC content

All Cerakote coatings are VOC compliant under the EPA and have low to no VOC content. To find out the VOC content of an individual coating please contact sds@nicindustries.com for more information.

PRISMATIC Powders<u>.</u> CERAKOTE _p

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

AHW-104 Rapid Ceramic Paint Sealant Revision: 07/23/2024

Version number: 3.1

National inventories

Country	Inventory	Status
AU	AIIC	Not all ingredients are listed
CA	DSL	Not all ingredients are listed
CA	NDSL	Not all ingredients are listed
CN	IECSC	Not all ingredients are listed
EU	ECSI	Not all ingredients are listed
EU	REACH Reg.	Not all ingredients are listed
JP	CSCL-ENCS	Not all ingredients are listed
JP	ISHA-ENCS	Not all ingredients are listed
KR	KECI	Not all ingredients are listed
MX	INSQ	Not all ingredients are listed
NZ	NZIoC	Not all ingredients are listed
PH	PICCS	Not all ingredients are listed
TR	CICR	Not all ingredients are listed
TW	TCSI	All ingredients are listed
US	TSCA	All ingredients are listed (ACTIVE)
TR	CICR TCSI	Not all ingredients are listed All ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

Revision: 07/23/2024

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Sub- stances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2023	From ACGIH®, 2023 TLVs® and BEIs® Book. Copyright 2023. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presenta-tions/tlv-bei-position-statement
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LHS	Lower hazard substance
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average



acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

AHW-104 Rapid Ceramic Paint Sealant

Version number: 3.1

Revision: 07/23/2024

Abbr.	Descriptions of used abbreviations
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).