

Ceramic Glass Coat Protectant

Safety Data Sheet

Version number: 1.0

SECTION 1: Identification

1.1 **Product identifier**

Trade name

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

1.3 Details of the supplier of the safety data sheet

PRISMATIC

NIC Industries, Inc 7050 6th St. White City Oregon 97503 United States

Telephone: 866-774-7628 e-mail: sds@nicindustries.com Website: www.nicindustries.com

1.4 **Emergency telephone number**

Emergency information service

The information contained in this Safety Data Sheet (SDS) is, to the best of our knowledge, true and accurate and presented in good faith. NIC Industries, Inc. makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. Because many factors may affect processing or application/use of this product, this data is offered solely for the user's consideration, investigation and verification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or process. Regulatory requirements are subject to change and may differ from one location to another. It is the responsibility of the buyer/user to ensure its activities comply with all local, state and federal regulations.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Hazard class and category code(s)

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
A.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
A.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
A.4S	Skin sensitization	1	Skin Sens. 1	H317
A.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
A.10	Aspiration hazard	1	Asp. Tox. 1	H304
B.7	Flammable solid	1	Flam. Sol. 1	H228

For full text of abbreviations: see SECTION 16.

Date of compilation: 05/08/2024

acc. to 29 CFR 1910.1200 App D INNOVATIONS OF NIC INDUSTRIES



1-800-633-8253 (USA & Canada)

Ceramic Glass Coat Protectant

General use



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word **DANGER**
- Pictograms

GHS02, GHS07, GHS08



- Hazard statements

H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

- Precautionary statements

r recautionary state	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	lf in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

Refractory Resin, Curable Resin, Curable Resin 2

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\ge 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \ge 0.1%.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%
Curable Resin	CAS No Trade Secret	50 - < 75
Curable Resin 2	CAS No Trade Secret	25 - < 50
Refractory Resin	CAS No Trade Secret	1-<5
Catalyst	CAS No Trade Secret	0 - < 0.1
70% Isopropanol	CAS No 67-63-0	0 - < 0.1

Remarks

** Trade Secret: In accordance with OSHA Hazard Communication Standard 29 CFR 1910.1200(i) and in accordance with the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS), the specific identity and/or exact percentage (concentration) of the composition has been withheld as a "Trade Secret"

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Water spray, Dry extinguishing powder, BC-powder, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder.

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Flammability hazards

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of substance	ldentifi- er	TWA [ppm]	TWA [mg/ m ³]	STEL [ppm]	STEL [mg/ m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	Curable Resin	TLV®	300							ACGIH® 2024
US	70% Isopropanol	TLV®	200		400					ACGIH® 2024
US	70% Isopropanol	PEL (CA)	400	980	500	1,225				Cal/OSHA PEL
US	70% Isopropanol	REL	400 (10 h)	980 (10 h)	500	1,225				NIOSH REL
US	70% Isopropanol	PEL	400	980						29 CFR 1910.100 0

Notation

Ceiling-C STEL

TWA

ceiling value is a limit value above which exposure should not occur

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-

time-weighted average (long-term exposure li weighted average (unless otherwise specified



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

8.2 Exposure controls

Appropriate engineering controls General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Moistened towelette
Color	Off-white
Particle	Not relevant (liquid)
Particle size	Not available
Odor	Characteristic

Other safety parameters

pH (value)	Not determined
Melting point/freezing point	Not determined
Initial boiling point and boiling range	93.3 °C
Flash point	Not applicable
Evaporation rate	Not determined
Flammability (solid, gas)	Not relevant (fluid) Flammable solid in accordance with GHS criteria



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

Explosive limits	Not determined
Vapor pressure	114.6 mmHg at 37.8 °C
Density	0.73 ^g / _{cm³}
Vapor density	Not available
Relative density	Not available
Solubility(ies)	Not determined
Partition coefficient	
- n-octanol/water (log KOW)	Not available
Auto-ignition temperature	>200 °C
Decomposition temperature	Not relevant
Viscosity	Not determined
- Kinematic viscosity	Not determined
Explosive properties	None
Oxidizing properties	None

There is no additional information

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment:
	200°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition. Reacts with water.

If heated:

Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Moisture.

10.5 Incompatible materials

Oxidizers. Alcohols. Amines. Water.

10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide, and silicon oxides may be produced from all coating formulations. Chlorine-containing gases, fluorine-containing gases may be produced in products containing p-chlorobenzotrifluoride. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ΑΤΕ
Refractory Resin	Trade Secret	Oral	>300 ^{mg} / _{kg}

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans				
Name of substance Classification Number				
70% Isopropanol 3				

Legend

Not classifiable as to carcinogenicity in humans



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of \geq 0.1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \ge 0.1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/packaging disposal

Do not empty into drains. Avoid release to the environment. Contact a licensed professional waste disposal service to dispose of this material and its packaging.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Hazardous waste code(s)

The waste code(s) should be assigned in discussion between the user and the waste disposal company.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

14.1	UN number			
	DOT	UN 3175		
	IMDG-Code	UN 3175		
	ICAO-TI	UN 3175		
4.2	UN proper shipping name			
	DOT	Solids containing flammable liquid, n.o.s.		
	IMDG-Code	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.		
	ICAO-TI	Solids containing flammable liquid, n.o.s.		
	Technical name (hazardous ingredients)	Curable Resin, Refractory Resin		
14.3	Transport hazard class(es)			
	DOT	4.1		
	IMDG-Code	4.1		
	ICAO-TI	4.1		
14.4	Packing group			
	DOT	II		
	IMDG-Code	II		
	ICAO-TI	II		
4.5	Environmental hazards	hazardous to the aquatic environment		
	Environmentally hazardous substance (aquatic environment)	Curable Resin		
14.6	Remarks			
14.7	Transport in bulk according to IMO instruments The cargo is not intended to be carried in bulk.			
	Information for each of the UN Model Regulations			
	Transport of dangerous goods by road or rail (49	-		
	Particulars in the shipper's declaration	UN3175, Solids containing flammable liquid, n.o.s		

Reportable quantity (RQ) Danger label(s)



Environmental hazards Special provisions (SP) UN3175, Solids containing flammable liquid, n.o.s., (contains: Curable Resin, Refractory Resin), 4.1, II, environmentally hazardous

1,659 lbs (753.3 kg) (Curable Resin)

4.1, fish and tree

YeS (hazardous to the aquatic environment) 47, IB6, IP2, T3, TP33



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

133

14.8 Remarks

ERG No

Special Provision 47: Mixtures of solids that are not subject to this subchapter and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Except when the liquids are fully absorbed in solid material contained in sealed bags, for single packagings, each packaging must correspond to a design type that has passed a leakproofness test at the Packing Group II level. Small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to this subchapter provided there is no free liquid in the packet or article.

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	Yes (hazardous to the aquatic environment) (Curable Resin)
Danger label(s)	4.1, fish and tree
Special provisions (SP)	216, 274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 kg
EmS	F-A, S-I
Stowage category	В
International Civil Aviation Organization (ICAO-I	ATA/DGR) - Additional information
Environmental hazards	Yes (hazardous to the aquatic environment)
Danger label(s)	4.1
Special provisions (SP)	A46
Excepted quantities (EQ)	E2
Limited quantities (LQ)	5 kg

14.9 Remarks

Special Provision A46: Mixtures of solids which are not subject to these Instructions and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, providing there is no free liquid visible at the time the substance is packaged and, for single packagings, the packaging must pass a leak-proofness test at the Packing Group II level. Sealed packets and articles containing less than 10 mL of a Packing Group II or III flammable liquid absorbed into a solid material are not subject to these Instructions provided there is no free liquid in the packet or articles.

Date of compilation: 05/08/2024



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)All ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

None of the ingredients are listed.

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listi	ngs		
Name of substance CAS No Effective date			
70% Isopropanol	67-63-0	12/31/1986	

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	Remarks	Statutory code	Final RQ pounds (Kg)
Curable Resin		3	1000 (454)

Legend

"3" indicates that the source is section 112 of the Clean Air Act

Clean Air Act

None of the ingredients are listed.

Right to Know Hazardous Substance List

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	De Minimis Concentration Threshold
70% Isopropanol	1.0 %
Curable Resin	1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	References	Remarks
Curable Resin	Ν	
Curable Resin 2	Ν	

Legend

National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards,"
 August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

- Hazardous Substance List (NJ-RTK)

Name of substance	Classifications
70% Isopropanol	F3
Curable Resin	F3

Legend

F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Classification
70% Isopropanol	E
Curable Resin	

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	References
70% Isopropanol	T, F
Catalyst	Т
Curable Resin	T, F

Legend

Flammability (NFPA®)

Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

None of the ingredients are listed.

VOC content

All Cerakote coatings are VOC compliant under the EPA and have low to no VOC content. To find out the VOC content of an individual coating please contact sds@nicindustries.com for more information.

National inventories

Country	Inventory	Status
AU	AIIC	Not all ingredients are listed
CA	DSL	Not all ingredients are listed
CA	NDSL	Not all ingredients are listed
CN	IECSC	Not all ingredients are listed
EU	ECSI	Not all ingredients are listed
EU	REACH Reg.	Not all ingredients are listed



Version number: 1.0

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

INNOVATIONS OF NIC INDUSTRIES

PRISMATIC

Ceramic Glass Coat Protectant

Date of compilation: 05/08/2024

Country	Inventory	Status
JP	CSCL-ENCS	Not all ingredients are listed
JP	ISHA-ENCS	Not all ingredients are listed
KR	KECI	All ingredients are listed
MX	INSQ	Not all ingredients are listed
NZ	NZIoC	All ingredients are listed
PH	PICCS	Not all ingredients are listed
TR	CICR	Not all ingredients are listed
TW	TCSI	All ingredients are listed
US	TSCA	All ingredients are listed (ACTIVE)

Legend

Legena	
AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIOC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Sub- stances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2024	From ACGIH®, 2024 TLVs® and BEIs® Book. Copyright 2024. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presenta-tions/tlv-bei-position-statement
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
- P	



PRISMATIC POWDERS Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

Abbr.	Descriptions of used abbreviations
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Ceramic Glass Coat Protectant

Version number: 1.0

Date of compilation: 05/08/2024

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.